

Normal Inverse Gaussian (NIG) model for Stochastic volatility

Parametrization

The NIG likelihood for stochastic volatility models is defined as:

$$\pi(y|\eta) = \sigma\epsilon$$

where

$$\epsilon \sim \text{NIG}(\beta, \psi)$$

and $\text{NIG}(\beta, \psi)$ is a standardised NIG distribution with density

$$\pi(\cdot|\beta, \psi) = \frac{\gamma\psi}{\pi} \sqrt{\frac{\beta^2 + \psi^2}{(\gamma x + \beta)^2 + \psi^2}} \exp\left(\psi^2 + \beta(\gamma x + \beta)\right) K_1\left(\sqrt{(\beta^2 + \psi^2)((\gamma x + \beta)^2 + \psi^2)}\right)$$

where $\gamma^2 = 1 + \beta^2/\psi^2$.

Link-function

The squared scale parameter σ is linked to the linear predictor η as:

$$\sigma^2 = \exp(\eta)$$

Hyperparameters

The skewness parameter β is represented as:

$$\theta_1 = \beta$$

and the shape parameter ψ as

$$\theta_2 = \log(\psi - 1)$$

as the prior is defined on $\theta = (\theta_1, \theta_2)$

Specification

- `family="stochvol.nig"`
- Required argument: y .

Hyperparameter spesification and default values

doc The Normal inverse Gaussian stochvol likelihood

hyper

theta1

hyperid 84001

name skewness

short.name skew

initial 0

fixed FALSE

prior gaussian

param 0 10

```

    to.theta function(x) x
    from.theta function(x) x
theta2
  hyperid 84002
  name shape
  short.name shape
  initial 0
  fixed FALSE
  prior loggamma
  param 1 0.5
  to.theta function(x) log(x - 1)
  from.theta function(x) 1 + exp(x)

```

survival FALSE

discrete FALSE

link default log

pdf stochvolnig

Example

In the following example we specify the likelihood for the stochastic volatility model to be NIG

```

#simulated data
n=500
phi=0.53
eta=rep(0.1,n)
for(i in 2:n)
  eta[i]=0.1+phi*(eta[i-1]-0.1)+rnorm(1,0,0.6)
y=exp(eta/2)*rnorm(n)
time=1:n
data=list(ret=y,time=time)

#fit the model
formula=ret~f(time,model="ar1")
result=inla(formula,family="stochvol.nig",data=data)

```

Notes

None