

New 0inflated models: Poisson & Binomial

Parametrisation

This is a new implementation (Nov'22) of zero-inflated Poisson, Binomial and negative Binomial likelihood, where we will allow for a linear predictor in both the zero-inflation and in the mean, but one of them needs to consist of fixed effects only. This means the setup will be somewhat different than for other likelihood models.

Details

The zero-inflated likelihood $f_0(y|\dots)$ is defined as

$$f_0(y|\eta_1, \eta_2) = p(\eta_1)1_{[y=0]} + (1 - p(\eta_1))f(y|\eta_2)$$

where $f(y|\dots)$ is either Poisson, Binomial or negative Binomial. We allow for two linear predictors in the model, but one needs to be “simple” (i.e. only consists of fixed effects). The other is general and defined via the formula. Normally, the zero-inflation probability is simpler (`family="0..."`)

$$\eta_1 = \text{simple} \quad \eta_2 = \text{formula}$$

but they can also be swapped (`family="0...S"`)

$$\eta_1 = \text{formula} \quad \eta_2 = \text{simple}$$

Link-function

This is similar to Poisson, Binomial and negative Binomial.

The link-function for the 'simple'-model must be given by argument `link.simple` in the `control.family`-argument. Only link-models without covariates/parameters are currently available. The examples later on show how this is done.

Hyperparameters

All parameters in the simple model are treated as hyperparameters. The j 'th element of η_1 is

$$(\eta_1)_j = \sum_{i=1}^m \beta_i x_{ij}$$

for covariates $x_1, \dots$, where m is maximum 10. An intercept in this model has to be defined manually by adding a constant covariate vector.

New 1inflated models for Poisson

There are two similar models for the Poisson based on the “conditioned to be positive” Poisson $f(y|y > 0)$. These ones are named `"1poisson"` and `"1poissonS"` and are 1-inflated.

Specification

- `family="0poisson"`
- `family="0poissonS"`
- `family="0binomial"`
- `family="0binomialS"`

- `family="0nbinomial"`
- `family="0nbinomialS"`
- `family="1poisson"`
- `family="1poissonS"`
- Required arguments: As for the Poisson, Binomial and negative Binomial (but how these arguments are given, will differ). Optional argument `link.simple`.
For negative Binomial, only variant 0 and 1 are supported.

Hyperparameter specification and default values

Opoisson

doc New 0-inflated Poisson

hyper

theta1

hyperid 56201
name beta1
short.name beta1
output.name beta1 for Opoisson observations
output.name.intern beta1 for Opoisson observations
initial -4
fixed FALSE
prior normal
param -4 10
to.theta function(x) x
from.theta function(x) x

theta2

hyperid 56202
name beta2
short.name beta2
output.name beta2 for Opoisson observations
output.name.intern beta2 for Opoisson observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta3

hyperid 56203
name beta3
short.name beta3
output.name beta3 for Opoisson observations
output.name.intern beta3 for Opoisson observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta4

hyperid 56204
name beta4
short.name beta4
output.name beta4 for Opoisson observations
output.name.intern beta4 for Opoisson observations
initial 0
fixed FALSE

```

    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta5
    hyperid 56205
    name beta5
    short.name beta5
    output.name beta5 for Opoisson observations
    output.name.intern beta5 for Opoisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta6
    hyperid 56206
    name beta6
    short.name beta6
    output.name beta6 for Opoisson observations
    output.name.intern beta6 for Opoisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta7
    hyperid 56207
    name beta7
    short.name beta7
    output.name beta7 for Opoisson observations
    output.name.intern beta7 for Opoisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 56208
    name beta8
    short.name beta8
    output.name beta8 for Opoisson observations
    output.name.intern beta8 for Opoisson observations
    initial 0
    fixed FALSE
    prior normal

```

```

    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta9
    hyperid 56209
    name beta9
    short.name beta9
    output.name beta9 for Opoisson observations
    output.name.intern beta9 for Opoisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta10
    hyperid 56210
    name beta10
    short.name beta10
    output.name beta10 for Opoisson observations
    output.name.intern beta10 for Opoisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x

survival FALSE
discrete TRUE
link default log quantile
link.simple default logit cauchit probit cloglog ccloglog
pdf 0inflated

```

OpoissonS

doc New 0-inflated Poisson Swap

hyper

theta1

hyperid 56301
name beta1
short.name beta1
output.name beta1 for OpoissonS observations
output.name.intern beta1 for OpoissonS observations
initial -4
fixed FALSE
prior normal
param -4 10
to.theta function(x) x
from.theta function(x) x

theta2

hyperid 56302
name beta2
short.name beta2
output.name beta2 for OpoissonS observations
output.name.intern beta2 for OpoissonS observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta3

hyperid 56303
name beta3
short.name beta3
output.name beta3 for OpoissonS observations
output.name.intern beta3 for OpoissonS observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta4

hyperid 56304
name beta4
short.name beta4
output.name beta4 for OpoissonS observations
output.name.intern beta4 for OpoissonS observations
initial 0
fixed FALSE
prior normal

```

    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta5
    hyperid 56305
    name beta5
    short.name beta5
    output.name beta5 for OpoissonS observations
    output.name.intern beta5 for OpoissonS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta6
    hyperid 56306
    name beta6
    short.name beta6
    output.name beta6 for OpoissonS observations
    output.name.intern beta6 for OpoissonS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta7
    hyperid 56307
    name beta7
    short.name beta7
    output.name beta7 for OpoissonS observations
    output.name.intern beta7 for OpoissonS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 56308
    name beta8
    short.name beta8
    output.name beta8 for OpoissonS observations
    output.name.intern beta8 for OpoissonS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10

```

```

    to.theta function(x) x
    from.theta function(x) x
theta9
  hyperid 56309
  name beta9
  short.name beta9
  output.name beta9 for OpoissonS observations
  output.name.intern beta9 for OpoissonS observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x
theta10
  hyperid 56310
  name beta10
  short.name beta10
  output.name beta10 for OpoissonS observations
  output.name.intern beta10 for OpoissonS observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x

survival FALSE
discrete TRUE
link default logit loga cauchit probit cloglog ccloglog loglog log sslogit logitoffset quantile pquantile
link.simple default log
pdf 0inflated

```

0binomial

doc New 0-inflated Binomial

hyper

theta1

hyperid 56401
name beta1
short.name beta1
output.name beta1 for 0binomial observations
output.name.intern beta1 for 0binomial observations
initial -4
fixed FALSE
prior normal
param -4 10
to.theta function(x) x
from.theta function(x) x

theta2

hyperid 56402
name beta2
short.name beta2
output.name beta2 for 0binomial observations
output.name.intern beta2 for 0binomial observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta3

hyperid 56403
name beta3
short.name beta3
output.name beta3 for 0binomial observations
output.name.intern beta3 for 0binomial observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta4

hyperid 56404
name beta4
short.name beta4
output.name beta4 for 0binomial observations
output.name.intern beta4 for 0binomial observations
initial 0
fixed FALSE
prior normal

```

    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta5
    hyperid 56405
    name beta5
    short.name beta5
    output.name beta5 for 0binomial observations
    output.name.intern beta5 for 0binomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta6
    hyperid 56406
    name beta6
    short.name beta6
    output.name beta6 for 0binomial observations
    output.name.intern beta6 for 0binomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta7
    hyperid 56407
    name beta7
    short.name beta7
    output.name beta7 for 0binomial observations
    output.name.intern beta7 for 0binomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 56408
    name beta8
    short.name beta8
    output.name beta8 for 0binomial observations
    output.name.intern beta8 for 0binomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10

```

```

    to.theta function(x) x
    from.theta function(x) x
theta9
  hyperid 56409
  name beta9
  short.name beta9
  output.name beta9 for 0binomial observations
  output.name.intern beta9 for 0binomial observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x
theta10
  hyperid 56410
  name beta10
  short.name beta10
  output.name beta10 for 0binomial observations
  output.name.intern beta10 for 0binomial observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x

survival FALSE
discrete TRUE
link default logit loga cauchit probit cloglog ccloglog loglog log
link.simple default logit cauchit probit cloglog ccloglog
pdf 0inflated

```

Opoisson

doc New 0-inflated Binomial Swap

hyper

theta1

```
hyperid 56501
name beta1
short.name beta1
output.name beta1 for ObinomialS observations
output.name.intern beta1 for ObinomialS observations
initial -4
fixed FALSE
prior normal
param -4 10
to.theta function(x) x
from.theta function(x) x
```

theta2

```
hyperid 56502
name beta2
short.name beta2
output.name beta2 for ObinomialS observations
output.name.intern beta2 for ObinomialS observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x
```

theta3

```
hyperid 56503
name beta3
short.name beta3
output.name beta3 for ObinomialS observations
output.name.intern beta3 for ObinomialS observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x
```

theta4

```
hyperid 56504
name beta4
short.name beta4
output.name beta4 for ObinomialS observations
output.name.intern beta4 for ObinomialS observations
initial 0
fixed FALSE
prior normal
```

```

    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta5
    hyperid 56505
    name beta5
    short.name beta5
    output.name beta5 for 0binomialS observations
    output.name.intern beta5 for 0binomialS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta6
    hyperid 56506
    name beta6
    short.name beta6
    output.name beta6 for 0binomialS observations
    output.name.intern beta6 for 0binomialS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta7
    hyperid 56507
    name beta7
    short.name beta7
    output.name beta7 for 0binomialS observations
    output.name.intern beta7 for 0binomialS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 56508
    name beta8
    short.name beta8
    output.name beta8 for 0binomialS observations
    output.name.intern beta8 for 0binomialS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10

```

```

    to.theta function(x) x
    from.theta function(x) x
theta9
  hyperid 56509
  name beta9
  short.name beta9
  output.name beta9 for 0binomialS observations
  output.name.intern beta9 for 0binomialS observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x
theta10
  hyperid 56510
  name beta10
  short.name beta10
  output.name beta10 for 0binomialS observations
  output.name.intern beta10 for 0binomialS observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x

survival FALSE
discrete TRUE
link default logit loga cauchit probit cloglog ccloglog loglog log
link.simple default logit cauchit probit cloglog ccloglog
pdf 0inflated

```

0binomial

doc New 0-inflated nBinomial

hyper

theta1

hyperid 56421
name beta1
short.name beta1
output.name beta1 for Onbinomial observations
output.name.intern beta1 for Onbinomial observations
initial -4
fixed FALSE
prior normal
param -4 10
to.theta function(x) x
from.theta function(x) x

theta2

hyperid 56422
name beta2
short.name beta2
output.name beta2 for Onbinomial observations
output.name.intern beta2 for Onbinomial observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta3

hyperid 56423
name beta3
short.name beta3
output.name beta3 for Onbinomial observations
output.name.intern beta3 for Onbinomial observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta4

hyperid 56424
name beta4
short.name beta4
output.name beta4 for Onbinomial observations
output.name.intern beta4 for Onbinomial observations
initial 0
fixed FALSE
prior normal

```

    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta5
    hyperid 56425
    name beta5
    short.name beta5
    output.name beta5 for Onbinomial observations
    output.name.intern beta5 for Onbinomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta6
    hyperid 56426
    name beta6
    short.name beta6
    output.name beta6 for Onbinomial observations
    output.name.intern beta6 for Onbinomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta7
    hyperid 56427
    name beta7
    short.name beta7
    output.name beta7 for Onbinomial observations
    output.name.intern beta7 for Onbinomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 56428
    name beta8
    short.name beta8
    output.name beta8 for Onbinomial observations
    output.name.intern beta8 for Onbinomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10

```

```

    to.theta function(x) x
    from.theta function(x) x
theta9
    hyperid 56429
    name beta9
    short.name beta9
    output.name beta9 for Onbinomial observations
    output.name.intern beta9 for Onbinomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta10
    hyperid 56430
    name beta10
    short.name beta10
    output.name beta10 for Onbinomial observations
    output.name.intern beta10 for Onbinomial observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x

survival FALSE
discrete TRUE
link default log
link.simple default logit cauchit probit cloglog ccloglog
pdf 0inflated

```

Opoisson

doc New 0-inflated nBinomialsS

hyper

theta1

hyperid 56441
name beta1
short.name beta1
output.name beta1 for OnbinomialsS observations
output.name.intern beta1 for OnbinomialsS observations
initial -4
fixed FALSE
prior normal
param -4 10
to.theta function(x) x
from.theta function(x) x

theta2

hyperid 56442
name beta2
short.name beta2
output.name beta2 for OnbinomialsS observations
output.name.intern beta2 for OnbinomialsS observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta3

hyperid 56443
name beta3
short.name beta3
output.name beta3 for OnbinomialsS observations
output.name.intern beta3 for OnbinomialsS observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta4

hyperid 56444
name beta4
short.name beta4
output.name beta4 for OnbinomialsS observations
output.name.intern beta4 for OnbinomialsS observations
initial 0
fixed FALSE
prior normal

```

    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta5
    hyperid 56445
    name beta5
    short.name beta5
    output.name beta5 for OnbinomialS observations
    output.name.intern beta5 for OnbinomialS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta6
    hyperid 56446
    name beta6
    short.name beta6
    output.name beta6 for OnbinomialS observations
    output.name.intern beta6 for OnbinomialS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta7
    hyperid 56447
    name beta7
    short.name beta7
    output.name beta7 for OnbinomialS observations
    output.name.intern beta7 for OnbinomialS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 56448
    name beta8
    short.name beta8
    output.name beta8 for OnbinomialS observations
    output.name.intern beta8 for OnbinomialS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10

```

```

    to.theta function(x) x
    from.theta function(x) x
theta9
  hyperid 56449
  name beta9
  short.name beta9
  output.name beta9 for OnbinomialS observations
  output.name.intern beta9 for OnbinomialS observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x
theta10
  hyperid 56450
  name beta10
  short.name beta10
  output.name beta10 for OnbinomialS observations
  output.name.intern beta10 for OnbinomialS observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x

survival FALSE
discrete TRUE
link default logit cauchit probit cloglog ccloglog
link.simple default log
pdf 0inflated

```

1poisson

doc New 1-inflated Poisson

hyper

theta1

hyperid 56401
name beta1
short.name beta1
output.name beta1 for 1poisson observations
output.name.intern beta1 for 1poisson observations
initial -4
fixed FALSE
prior normal
param -4 10
to.theta function(x) x
from.theta function(x) x

theta2

hyperid 56402
name beta2
short.name beta2
output.name beta2 for 1poisson observations
output.name.intern beta2 for 1poisson observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta3

hyperid 56403
name beta3
short.name beta3
output.name beta3 for 1poisson observations
output.name.intern beta3 for 1poisson observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta4

hyperid 56404
name beta4
short.name beta4
output.name beta4 for 1poisson observations
output.name.intern beta4 for 1poisson observations
initial 0
fixed FALSE
prior normal

```

    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta5
    hyperid 56405
    name beta5
    short.name beta5
    output.name beta5 for 1poisson observations
    output.name.intern beta5 for 1poisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta6
    hyperid 56406
    name beta6
    short.name beta6
    output.name beta6 for 1poisson observations
    output.name.intern beta6 for 1poisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta7
    hyperid 56407
    name beta7
    short.name beta7
    output.name beta7 for 1poisson observations
    output.name.intern beta7 for 1poisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 56408
    name beta8
    short.name beta8
    output.name beta8 for 1poisson observations
    output.name.intern beta8 for 1poisson observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10

```

```

    to.theta function(x) x
    from.theta function(x) x
theta9
  hyperid 56409
  name beta9
  short.name beta9
  output.name beta9 for 1poisson observations
  output.name.intern beta9 for 1poisson observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x
theta10
  hyperid 56410
  name beta10
  short.name beta10
  output.name beta10 for 1poisson observations
  output.name.intern beta10 for 1poisson observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x

survival FALSE
discrete TRUE
link default log quantile
link.simple default logit cauchit probit cloglog ccloglog
pdf 0inflated

```

1poissonS

doc New 1-inflated Poisson Swap

hyper

theta1

hyperid 56501
name beta1
short.name beta1
output.name beta1 for 1poissonS observations
output.name.intern beta1 for 1poissonS observations
initial -4
fixed FALSE
prior normal
param -4 10
to.theta function(x) x
from.theta function(x) x

theta2

hyperid 56502
name beta2
short.name beta2
output.name beta2 for 1poissonS observations
output.name.intern beta2 for 1poissonS observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta3

hyperid 56503
name beta3
short.name beta3
output.name beta3 for 1poissonS observations
output.name.intern beta3 for 1poissonS observations
initial 0
fixed FALSE
prior normal
param 0 10
to.theta function(x) x
from.theta function(x) x

theta4

hyperid 56504
name beta4
short.name beta4
output.name beta4 for 1poissonS observations
output.name.intern beta4 for 1poissonS observations
initial 0
fixed FALSE
prior normal

```

    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta5
    hyperid 56505
    name beta5
    short.name beta5
    output.name beta5 for 1poissonS observations
    output.name.intern beta5 for 1poissonS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta6
    hyperid 56506
    name beta6
    short.name beta6
    output.name beta6 for 1poissonS observations
    output.name.intern beta6 for 1poissonS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta7
    hyperid 56507
    name beta7
    short.name beta7
    output.name beta7 for 1poissonS observations
    output.name.intern beta7 for 1poissonS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 56508
    name beta8
    short.name beta8
    output.name beta8 for 1poissonS observations
    output.name.intern beta8 for 1poissonS observations
    initial 0
    fixed FALSE
    prior normal
    param 0 10

```

```

    to.theta function(x) x
    from.theta function(x) x
theta9
  hyperid 56509
  name beta9
  short.name beta9
  output.name beta9 for 1poissonS observations
  output.name.intern beta9 for 1poissonS observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x
theta10
  hyperid 56510
  name beta10
  short.name beta10
  output.name beta10 for 1poissonS observations
  output.name.intern beta10 for 1poissonS observations
  initial 0
  fixed FALSE
  prior normal
  param 0 10
  to.theta function(x) x
  from.theta function(x) x

survival FALSE
discrete TRUE
link default logit loga cauchit probit cloglog ccloglog loglog log sslogit logitoffset quantile pquantile
link.simple default log
pdf 0inflated

```

Example: 0Poisson

```
sim.poisson <- function(prob, m)
{
  stopifnot(length(prob) == length(m) && length(prob) > 0)
  n <- length(m)
  y <- numeric(n)
  event <- (runif(n) < prob)
  idx.zero <- which(event)
  idx.non.zero <- which(!event)
  y[idx.zero] <- 0
  y[idx.non.zero] <- rpois(length(idx.non.zero), lambda = m[idx.non.zero])
  return (y)
}

## chose link-function to use for the zero-inflation probability
link.simple <- "logit"
inv.link <- inla.link.invlogit
## link.simple <- "probit"
## inv.link <- inla.link.invprobit
## link.simple <- "cloglog"
## inv.link <- inla.link.invcloglog

n <- 1000
z <- rnorm(n, sd = 0.3)
x <- rnorm(n, sd = 0.2)
xx <- rnorm(n, sd = 0.3)
zz <- rnorm(n, sd = 0.2)
E <- runif(n, min = 0.8, max = 1/0.8)

beta <- c(1, 1.1, 2.1, 0, -2, 1.2, 2.2, 0)
eta2 <- beta[1] + beta[2] * xx + beta[3] * zz + beta[4] * xx * zz
eta1 <- beta[5] + beta[6] * x + beta[7] * z + beta[8] * x * z
prob <- inv.link(eta1)
m <- E*exp(eta2)

ok <- FALSE
while(!ok) {
  y <- sim.poisson(prob, m)
  ok <- !all(y == 0)
}

## head(data.frame(y, E, x, z, xx, zz))

r <- inla(
  inla.mdata(cbind(y, E), cbind(1, x, z, x*z)) ~ 1 + xx + zz + xx*zz,
  family = "0poisson",
  data = data.frame(y, E, x, z, xx, zz),
  control.fixed = list(prec = 1, prec.intercept = 1),
  control.compute = list(cpo = TRUE),
  control.family = list(link.simple = link.simple,
    hyper = list(beta1 = list(param = c(0, 1)),
      beta2 = list(param = c(0, 1)),
      beta3 = list(param = c(0, 1)),
      beta4 = list(param = c(0, 1)),
      beta5 = list(param = c(0, 1))))))

rr <- inla(
```

```

inla.mdata(cbind(y, E), cbind(1, xx, zz, xx*zz)) ~ 1 + x + z + x*z,
family = "0poissonS",
data = data.frame(y, E, x, z, xx, zz),
control.fixed = list(prec = 1, prec.intercept = 1),
control.compute = list(cpo = TRUE),
## in this case we need to define link.simple as the main link
control.family = list(control.link = list(model = link.simple),
                      hyper = list(beta1 = list(param = c(0, 1)),
                                   beta2 = list(param = c(0, 1)),
                                   beta3 = list(param = c(0, 1)),
                                   beta4 = list(param = c(0, 1)),
                                   beta5 = list(param = c(0, 1)))))

summary(r)
summary(rr)

res <- cbind("beta" = beta,
            "0poisson" = c(r$summary.fixed$mean, r$summary.hyperpar$mean),
            "0poissonS" = c(rr$summary.hyperpar$mean, rr$summary.fixed$mean))
res <- cbind(res,
            diff = (res[, 2]-beta),
            diffS = (res[, 3]-beta),
            "diff/sd" = (res[, 2]-beta) / c(r$summary.fixed$sd, r$summary.hyperpar$sd),
            "diffS/sd" = (res[, 3]-beta) / c(rr$summary.hyperpar$sd, rr$summary.fixed$sd))
mm <- nrow(res) %/% 2
rownames(res) <- c(paste0("beta", 1:mm, ".poisson"), paste0("beta", 1:mm, ".prob"))
print(round(dig = 2, res))

```

Example: 0Binomial

```
sim.binomial <- function(prob, p, size)
{
  ## - prob=zero-inflation-prob
  ## - binomial(size, p)
  stopifnot(length(prob) == length(p) && length(prob) == length(size)
            && length(prob) > 0)
  n <- length(prob)
  y <- numeric(n)
  event <- (runif(n) < prob)
  idx.zero <- which(event)
  idx.non.zero <- which(!event)
  y[idx.zero] <- 0
  y[idx.non.zero] <- rbinom(length(idx.non.zero),
                           size = size[idx.non.zero],
                           prob = p[idx.non.zero])

  return (y)
}

n <- 1000
z <- rnorm(n, sd = 0.3)
x <- rnorm(n, sd = 0.2)
xx <- rnorm(n, sd = 0.3)
zz <- rnorm(n, sd = 0.2)
Ntrials <- sample(1:10, n, replace = TRUE)

## chose link-function to use for the zero-inflation probability
link.simple <- "logit"
inv.link <- inla.link.invlogit
## link.simple <- "probit"
## inv.link <- inla.link.invprobit
## link.simple <- "cloglog"
## inv.link <- inla.link.invcloglog

beta <- c(1, 1.1, 2.1, 0, -2, 1.2, 2.2, 0)
eta2 <- beta[1] + beta[2] * xx + beta[3] * zz + beta[4] * xx * zz
eta1 <- beta[5] + beta[6] * x + beta[7] * z + beta[8] * x * z
prob <- inv.link(eta1)
p <- 1/(1 + exp(-eta2))

ok <- FALSE
while(!ok) {
  y <- sim.binomial(prob, p, Ntrials)
  ok <- !all(y == 0)
}

## head(data.frame(y, Ntrials, x, z, xx, zz))

r <- inla(
  inla.mdata(cbind(y, Ntrials), cbind(1, x, z, x*z)) ~ 1 + xx + zz + xx*zz,
  family = "0binomial",
  data = data.frame(y, Ntrials, x, z, xx, zz),
  control.fixed = list(prec = 1, prec.intercept = 1),
  control.compute = list(cpo = TRUE),
  control.family = list(link.simple = link.simple,
                        hyper = list(beta1 = list(param = c(0, 1)),
                                      beta2 = list(param = c(0, 1)),
```

```

beta3 = list(param = c(0, 1)),
beta4 = list(param = c(0, 1)),
beta5 = list(param = c(0, 1))))

rr <- inla(
  inla.mdata(cbind(y, Ntrials), cbind(1, xx, zz, xx*zz)) ~ 1 + x + z + x*z,
  family = "0binomialS",
  data = data.frame(y, Ntrials, x, z, xx, zz),
  control.fixed = list(prec = 1, prec.intercept = 1),
  control.compute = list(cpo = TRUE),
  ## in this case we need to define link.simple as the main link
  control.family = list(control.link = list(model = link.simple),
    hyper = list(beta1 = list(param = c(0, 1)),
      beta2 = list(param = c(0, 1)),
      beta3 = list(param = c(0, 1)),
      beta4 = list(param = c(0, 1)),
      beta5 = list(param = c(0, 1)))))

summary(r)
summary(rr)

res <- cbind("beta" = beta,
  "0binomial" = c(r$summary.fixed$mean, r$summary.hyperpar$mean),
  "0binomialS" = c(rr$summary.hyperpar$mean, rr$summary.fixed$mean))
res <- cbind(res,
  diff = (res[, 2]-beta),
  diffS = (res[, 3]-beta),
  "diff/sd" = (res[, 2]-beta) / c(r$summary.fixed$sd, r$summary.hyperpar$sd),
  "diffS/sd" = (res[, 3]-beta) / c(rr$summary.hyperpar$sd, rr$summary.fixed$sd))
mm <- nrow(res) %/% 2
rownames(res) <- c(paste0("beta", 1:mm, ".binomial"), paste0("beta", 1:mm, ".prob"))
print(round(dig = 2, res))

```

Example: 1Poisson

```
sim.1poisson <- function(prob, lambda) {
  stopifnot(length(prob) == length(lambda) && length(prob) > 0)
  n <- length(lambda)
  y <- numeric(n)
  event <- (runif(n) < prob)
  idx.one <- which(event)
  idx.non.one <- which(!event)
  y[idx.one] <- 1
  for(i in idx.non.one) {
    y[i] <- 0
    while(y[i] == 0) {
      yy <- rpois(20, lambda = lambda[i])
      if (any(yy > 0)) {
        y[i] <- yy[min(which(yy > 0))]
      }
    }
  }
  return (y)
}

## chose link-function to use for the zero-inflation probability
link.simple <- "logit"
inv.link <- inla.link.invlogit
## link.simple <- "probit"
## inv.link <- inla.link.invprobit
## link.simple <- "cloglog"
## inv.link <- inla.link.invcloglog

n <- 10^4
z <- rnorm(n, sd = 0.3)
x <- rnorm(n, sd = 0.2)
xx <- rnorm(n, sd = 0.3)
zz <- rnorm(n, sd = 0.2)
E <- runif(n, min = 0.1, max = 100)

beta <- c(1, 1.1, 2.1, 0, -2, 1.2, 2.2, 0)
eta2 <- beta[1] + beta[2] * xx + beta[3] * zz + beta[4] * xx * zz
eta1 <- beta[5] + beta[6] * x + beta[7] * z + beta[8] * x * z
prob <- inv.link(eta1)
lambda <- E*exp(eta2)

y <- sim.1poisson(prob, lambda)

## head(data.frame(y, E, x, z, xx, zz))

r <- inla(
  inla.mdata(cbind(y, E), cbind(1, x, z, x*z)) ~ 1 + xx + zz + xx*zz,
  family = "1poisson",
  data = data.frame(y, E, x, z, xx, zz),
  control.fixed = list(prec = 1, prec.intercept = 1),
  control.compute = list(cpo = TRUE),
  control.family = list(link.simple = link.simple,
    hyper = list(beta1 = list(param = c(0, 1)),
      beta2 = list(param = c(0, 1)),
      beta3 = list(param = c(0, 1)),
      beta4 = list(param = c(0, 1)),
```

```

beta5 = list(param = c(0, 1))))

rr <- inla(
  inla.mdata(cbind(y, E), cbind(1, xx, zz, xx*zz)) ~ 1 + x + z + x*z,
  family = "lpoissonS",
  data = data.frame(y, E, x, z, xx, zz),
  control.fixed = list(prec = 1, prec.intercept = 1),
  control.compute = list(cpo = TRUE),
  control.inla = list(cmin = 0),
  ## in this case we need to define link.simple as the main link
  control.family = list(control.link = list(model = link.simple),
    hyper = list(beta1 = list(param = c(0, 1)),
      beta2 = list(param = c(0, 1)),
      beta3 = list(param = c(0, 1)),
      beta4 = list(param = c(0, 1)),
      beta5 = list(param = c(0, 1)))))

summary(r)
summary(rr)

res <- cbind("beta" = beta,
  "lpoisson" = c(r$summary.fixed$mean, r$summary.hyperpar$mean),
  "lpoissonS" = c(rr$summary.hyperpar$mean, rr$summary.fixed$mean))
res <- cbind(res,
  diff = (res[, 2]-beta),
  diffS = (res[, 3]-beta),
  "diff/sd" = (res[, 2]-beta) / c(r$summary.fixed$sd, r$summary.hyperpar$sd),
  "diffS/sd" = (res[, 3]-beta) / c(rr$summary.hyperpar$sd, rr$summary.fixed$sd))
mm <- nrow(res) %/% 2
rownames(res) <- c(paste0("beta", 1:mm, ".poisson"), paste0("beta", 1:mm, ".prob"))
print(round(dig = 2, res))

```

Example: OnBinomial

```
sim.nbinom <- function(prob, m, size)
{
  stopifnot(length(prob) == length(m) &&
            length(size) == length(m) &&
            length(prob) > 0)
  n <- length(m)
  y <- numeric(n)
  event <- (runif(n) < prob)
  idx.zero <- which(event)
  idx.non.zero <- which(!event)
  y[idx.zero] <- 0
  y[idx.non.zero] <- rnbinom(length(idx.non.zero),
                           mu = m[idx.non.zero],
                           size = size[idx.non.zero])

  return (y)
}

## chose link-function to use for the zero-inflation probability
link.simple <- "logit"
inv.link <- inla.link.invlogit

variant <- 0
n <- 10^4
z <- rnorm(n, sd = 0.2)
x <- rnorm(n, sd = 0.2)
xx <- rnorm(n, sd = 0.2)
zz <- rnorm(n, sd = 0.2)
E <- runif(n, min = 0.5, max = 1/0.5)
if (variant == 1) {
  size = 3 * E
} else {
  size <- rep(3, n)
}

xxzz <- 0.2 * scale(xx * zz)
xz <- 0.2 * scale(x*z)
beta <- c(1, 1.1, 2.1, 0, -2, 1.2, 2.2, 0)
eta2 <- beta[1] + beta[2] * xx + beta[3] * zz + beta[4] * xxzz
eta1 <- beta[5] + beta[6] * x + beta[7] * z + beta[8] * xz
prob <- inv.link(eta1)
m <- E*exp(eta2)

ok <- FALSE
while(!ok) {
  y <- sim.nbinom(prob, m, size)
  ok <- !all(y == 0)
}

r <- inla(
  inla.mdata(cbind(y, E), cbind(1, x, z, xz)) ~ 1 + xx + zz + xxzz,
  family = "Onbinomial",
  data = data.frame(y, E, x, z, xz, xx, zz, xxzz),
  control.fixed = list(prec = 1, prec.intercept = 1),
  control.compute = list(cpo = TRUE),
  control.family = list(link.simple = link.simple, variant = variant,
                        hyper = list(beta1 = list(param = c(0, 1)),
```

```

beta2 = list(param = c(0, 1)),
beta3 = list(param = c(0, 1)),
beta4 = list(param = c(0, 1))))

##r <- inla.rerun(r)
summary(r)

rr <- inla(
  inla.mdata(cbind(y, E), cbind(1, xx, zz, xxzz)) ~ 1 + x + z + xz,
  family = "OnbinomialS",
  data = data.frame(y, E, x, z, xz, xx, zz, xxzz),
  control.fixed = list(prec = 1, prec.intercept = 1),
  control.compute = list(cpo = TRUE),
  control.inla = list(cmin = 0),
  ## in this case we need to define link.simple as the main link
  control.family = list(control.link = list(model = link.simple),
    hyper = list(beta1 = list(param = c(0, 1)),
      beta2 = list(param = c(0, 1)),
      beta3 = list(param = c(0, 1)),
      beta4 = list(param = c(0, 1)))))

##rr <- inla.rerun(rr)

summary(r)
summary(rr)

ress <- cbind("beta" = beta,
  "Onbin" = c(r$summary.fixed$mean, r$summary.hyperpar$mean[-1]),
  "OnbinS" = c(rr$summary.hyperpar$mean[-1], rr$summary.fixed$mean))
res <- cbind(ress,
  diff = (ress[, 2]-beta),
  diffS = (ress[, 3]-beta),
  "sd" = c(r$summary.fixed$sd, r$summary.hyperpar$sd[-1]),
  "sdS" = c(rr$summary.hyperpar$sd[-1], rr$summary.fixed$sd),
  "diff/sd" = (ress[, 2]-beta) / c(r$summary.fixed$sd, r$summary.hyperpar$sd[-1]),
  "diffS/sd" = (ress[, 3]-beta) / c(rr$summary.hyperpar$sd[-1], rr$summary.fixed$sd))
mm <- nrow(res) %/% 2
rownames(res) <- c(paste0("beta", 1:mm, ".nbin"), paste0("beta", 1:mm, ".prob"))
print(round(dig = 3, res))

round(dig = 3, rbind(r$summary.hyperpar[1,c(1, 2, 6)],
  rr$summary.hyperpar[1,c(1, 2, 6)]))
plot(r$cpo$pit, rr$cpo$pit)
abline(a=0,b=1,lwd=3,col="blue")
coef(lm(r$cpo$pit ~ rr$cpo$pit))

```